



move forward



Name: Uranus Cordless Phone

Model: HWD9888(38)TSD-5S

Uranus

BITTEL ELECTRONICS CO., LTD.

www.bittelcom.com



1 Line Speaker Cordless Phone
 CID display cordless phone, supporting DTMF/FSK system
 One Base-station supports up to 3 handsets
 Support 2.4GHz DCT China, DECT1.8GHz International, DECT6.0 Domestic
 Without external power, the Base can receive and make calls by SPKR normally
 Digital code transmission, avoids mutual interference with other electronic equipments
 Handset recharges the battery rapidly
 Stand by Time(PP): 7 days
 Talk Time(PP): 10 hours
 Handset Range: 200m from Base
 Handset detects the Battery power, and warns if low battery
 Handset warns in case beyond the operation distance
 Both the Base and the Handset, Ringer and Volume are adjustable
 Flash, Redial and Hold both for the Handset and the Unit
Magnetic Hook Switch™, achieve the better waterproof
Faceplate Plus™, full length faceplate and placard faceplate
AutoConnect™, Busy tone disconnected automatically for both Base Unit and Handset
EZ Message Light™, Message Waiting Light with retrieval function
Auto-Gone CID™, the CID number disappearing after 60 seconds
PrivacyGuard™, Last dialed number disappearing after a definite time
 10/5/3/0 **Guest Service keys™**, Permanent one-touch memory keys
Express Programmer™, Support Remote Programming Master Cloner and Hand-held Programming Cloner

Specifications:

Frequency Hopping Spread Spectrum (FHSS)
 Average Transmission Power: 4mW
 Modulation Method: GFSK
 The Physical Layer Uses: TDMA
 Dial Character: Standard 12 group(DTMF)
 Out Power: 22dBm
 Receiver Sensitivity: ≤ -85 dBm
 NTP Power: 20+4/-2 dBm
 Power(FP): 9VDC adapter
 Standby Time(PP): 7 days
 Talk Time(PP): 10 hours
 Battery SPEC: NI-MH 3.6V 700mA
 Talk on current: 40~50mA(PP)
 Charge current: 140~150mA(PP)
 Temperature: -10℃~40℃
 Humidity: 10%~95%

Flash time: 100ms~1000ms optional 100ms. Standard 600ms
 Message Waiting Light Voltage :
 1. Standard 90~150V DC
 2. Customized various MWL card compatible with PBX:
 AVAYA, Siemens, Philips, Alcatel, NEC, Nortel,
 Mitel, Panasonic, etc.
 Quality Control: ISO9001, ISO14001
 Quality Approval: CCC, FCC, CE, RoHS
 FCC rules: The unit complies with part 15 and part 68 of
 the FCC rules and regulations
 One-Touch Memory Key Programming :
 Manually Store(✓) Hand-held Cloner R.P.(✓) Master
 Cloner on line((×)
 Box Dimension: 50×42.5×31(cm)
 Package (set/carton): 10set/Carton



Guest Service Keys™

Traditionally, people usually adopt the large capacitor to store the one-touch programmed number, but it's easy to lose the stored numbers after a longer time. Bittel new hotel guestroom phone adopts E2PROM combining software "One-Touch" memory programmed technology, the stored numbers are just like the numbers stored in the computer hard disk, never lose, with the powerful reliability. It's really the permanent memory keys.



EZ Message Light™

"MWL with message retrieval function": Traditional voice mail service is very troublesome. Guest doesn't know how to use when MWL flashes. While our new MWL adopts patented technology of "light and key in one", guest touches and retrieves message when the red MWL flashes, very convenient, simple and quick.