



Name: Safe View Phone

Model: HCD9888(40)TSD-VB



Doorbell Calling Function.
Busy tone disconnecting automatically.
One-touch memory cloner /R.P. memory master cloner.
Vivid Display of Colored TFT Liquid Version.
Ringer Volume--- Ringer volume control: HIGH, LOW, OFF.
Hearing Aid Compatible Handset.
Handset Jack---Module Jack to connect handset cord from handset to telephone.
One-touch memory key---Used to dial the memory keys by one touch and to increase some other special functions(32 digits length at most).
[VOL]Key----Key adjust handset and speaker (on base) volume level[Normal-Medium-High-Normal]
REDIAL Keys---Dial the last number dialed .
FLASH key---Enters 600ms hook switch flash.
R Keys---Enters 100ms hook switch flash for accessing special telephone system features matching PBX.
Hold button - Places current caller on hold (with LED indicator).
[STORE] Key -Hidden key for storing numbers to memory keys.
[PAUSE] Key ---Hidden key inserts a 3.6 second pause in stored numbers.
[SPKR] Key ---Activates speakerphone function
Mute button - Shuts off all sending sound without hanging up on caller.
[MON] Key-Monitor outside the room.

Specifications:

Dimension: 23x19.5x9.6 cm
Handset cord: 3.66m
Line cord: 4.58m
Weight: 3kg/set
Color: Ivory、 Black optional
Handset: Hearing Aid Compatible Handset
Dial Character: Standard 12 group (DTMF)
Flash time: 100ms~1000ms optional standard 600ms
Message Waiting Light Voltage: Standard 90~150V DC;
Various PBX compatible customized
Operating Voltage: 24V~60V DC
Quality Control: ISO9001

One-Touch Memory Key Programming : Manually Store(✓)
Hand-held Cloner R.P.(✓) Master Cloner on line(✓)
Gift Box: 28.80x 24.20X 10.01(cm)
Master Carton: 49X 41.5X 30.5 (cm)
Package: 2 gift boxes /set ; 4 sets/ Carton
3-inch TFT LCD color displaying with high resolution
Video Converter DC 12V power input
Camera AV cable: Dedicated video cable with the shield
Monitor power cable
Voice cable :4/6-pin PSTN telephone line with 15meters. the diameter is 7X0.12 core line